

**Product datasheet**

# 14 dB, 2.4 GHz Wireless Platform

**Product code:** RFT-ENC-14-24-XX

**Version:** 05-.2008

**RFTechnics Limited**

 Whitehall House  
 2 Queens Road  
 Sheffield S2 4DG UK

T: +44 (0)114 270 08 87

F: +44 (0)797 725 42 81

E: sales@rftechnics.com

**RFTECHNICS.COM**
**Application:** External AP, Point to point, Point to multipoint for 802.11b/g

- Allows integration of customer's radio equipment
- Optional RF connector interfaces available (RPTNC, RPSMA, U-FL) for the internal antenna
- Fitted with a powerful 14 dB internal antenna
- Provision for a 2nd external antenna via N-type connector (for Omni, or higher Gain Antenna)
- Maintains excellent RF performance across frequency band
- Rugged, weather proof enclosure suitable for harsh environment
- Supplied with RJ45 Ethernet Connector and splitter board for easy connectivity
- Supplied with Passive POE injector as part of the kit
- Comes with complete tilt bracket for pole mounting, for easy deployment
- Complete kit individually Boxed

**Technical specification**
**Electrical**

Frequency Band:	2400 - 2500 MHz
Gain:	14 dBi minimum
Polarisation:	Vertical or Horizontal (Optional)
3 dB Beamwidth Horizontal Plane:	32°
3 dB Beamwidth Vertical Plane:	32°
Front to Back Ratio:	25 dB
Nominal Impedance:	50 Ohm
VSWR:	1.5:1.0 max.
Maximum Input Power:	20 W
Connector Type for Internal Antenna:	Options: 01- RPTNC, 02 - RPSMA, 03 - U-FL
Connector Type for external Antenna:	N-Type female
Application:	Access Point, Point to Multipoint for 802.11b/g

**Mechanical**

Appearance:	Flat Panel
Size (W x H x D):	230 mm x 230 mm x 90 mm
Weight:	800 g
Operating Temperature:	-40° C to +70° C
Wind Loading:	130 mph (210 km/h)

**Materials**

Covering Material:	UV stabilised ABS Plastic
Colour	Grey
Mounting Method	Galvanised steel bracket set for mast or pole mounting 1.2 - 2.5 in (30 - 62 mm). Comes complete with elevation tilt angle mechanism



Enclosure with Pc-Engines WRAP Board



Enclosure with Buffalo-WHR54GS Board



External N-Type connector and RJ45 protected ethernet connection



Tilting Bracket + U bolt and saddle for pole mounting up to 2"



Passive POE injector

Prices and specifications are subject to change without notice.

Copyright © RFTechnics Ltd, All rights reserved.

All trademarks herein are the property of their respective owners.